



GRIP^{line} SUPER56

- Hydraulic spindle with double speed and double rotation
- Hydraulic fitting carriage sliding
- Hydraulic control unit with adjustable pressure
- Four patented clamping jaws for a precise gripping. Suitable for different positions
- Bead breaking fast rotation with pneumatic system
- Bead breaking force 26500 N

DATASHEET



Spindle tightening inward 14" - 56"



Tire width max 1300 mm



Maximum tire diameter 2300 mm



Rotation speed 4,5 - 9 rpm



Weight 1000 kg



Dimensions (H x D x L) 1750 x 2150 x 2500 mm



Wooden crate packaging (H x D x L) 1025 x 2250 x 1950 mm



Made in Italy

The picture shows GRIP Super 52

ARTICLE / DESCRIPTION

7010 GRIP SUPER 56
Power supply: 3-phase
400v - 50/60 Hz

STANDARD ACCESSORIES



- Mounting lever 500 mm
- Long mounting lever
- Rim clamp for aluminum rims

EXTRA OPTIONS FOR TIRE CHANGERS GRIP SUPER 56



ART. 7051

- Protective jaws for aluminium rims, set of six



ART. 7053

- Clamping jaw extension, set of six, up to 60"



ART. 7055

- Rim clamp for aluminium rims



ART. 7056

- Aluminium protection jaws, set of 4, for fitting to the clamps jaws



ART. 7050

- Inflating box for truck tires