

ROLLline R8TRUCK

- TFT Monitor showing programs
- 5 specific programs for truck wheels
- Internal electronic measuring arm for rim distance & diameter
- Easyfit internal electronic measuring arm and a complete software package including all static and dynamic balancing programs
- Standard pneumatic lift for wheel-mounting
- Threaded screw 40 mm
- Max wheel weight 200 kg
- Automatic balancing speed based on wheel weight

INSTALLATION VIDEO
INSTRUCTIONS AVAILABLE



Made in Italy

DATASHEET

| | |
|--|---------------------------------------------------------------|
| | Accuracy 1 gr auto - 10 gr camion |
| | Working pressure 8 - 12 bar |
| | Tire width min 1" - max 24" |
| | Tire diameter min 6" - max 40" |
| | Rotation speed 100/200 rpm |
| | Max wheel weight 200 kg |
| | Weight 310 kg |
| | Dimensions (H x D x L) 1870 x 1270 x 2040 mm |
| | Cardboard box packaging (H x D x L) 1210 x 950 x 1900 mm |

STANDARD ACCESSORIES



- Threaded screw with block 40 mm
 - Quick nut
- 4 cones from 43 to 110 mm



- Truck precision flange with 4- and 5-arm centring system



- Weight pliers
- Calibration weight
- Weights removal blade
- Weight sample

ARTICLE / DESCRIPTION

| | |
|-------------|----------------------------------------------------------------------|
| 8050 | ROLL R8 TRUCK Power supply: Single-phase 220v - 50/60Hz |
|-------------|----------------------------------------------------------------------|

EXTRA OPTIONS FOR WHEEL BALANCER ROLL R8 TRUCK



ART. 8204

- 9 precision bushes kit from 52,5 to 122 mm



ART. 8205

- Flange kit for ring without central hole



ART. 8210

- Lockring cap



ART. 7050

- Inflating box for truck tires